

Rapiscan 520B

Rapiscan[®]
systems

An OSI Systems Company

BAGGAGE AND PARCEL INSPECTION

Dual Energy

Full Featured

Dependable

Large Parcels



The dual energy **Rapiscan 520B** is our most widely deployed X-ray system. Dual energy imaging provides automatic color coding of materials with different atomic numbers so that screeners can easily identify objects within the parcel. The dependable **520B** offers a full range of options and excellent image quality.

The **Rapiscan 520B** has a large tunnel opening of 640mm (25.2 inches) wide by 430mm (16.93 inches) high.

CUSTOMER SUPPORT SERVICES

Our team is dedicated to providing a prompt, effective and personalized response that exceeds your expectations. With spare parts inventory and skilled technicians all over the world, you can be certain Rapiscan Systems will always be prepared with a solution to address your requirements. By measuring response time, parts delivery and support status, our team embraces a customer centric philosophy to ensure continual improvement of our products and services.

FEATURES & OPTIONS

Threat Image Projection (TIP):

TIP inserts digital threat images at configurable frequencies into the regular flow of bags. TIP is a reliable method for continually improving the skill level of screeners and is the preferred training method used by regulatory agencies worldwide.

Network Display Station (NDS):

NDS improves threat detection, throughput, and simplifies operating procedures by enabling the operator performing a manual search of suspect bags to reconcile the actual bag contents with the scanned image.

Network Management System

(NMS): Allows a supervisor to monitor the performance of many X-ray checkpoints in a large facility from a single location.

Enhanced Performance X-ray

(EPX): Enables consistent detection of materials having characteristics of explosives, narcotics, gold, currency and agricultural products.

Operator Training Program

(OTP): OTP enables the X-ray system to be used as a training terminal without running parcels.



ONE COMPANY - TOTAL SECURITY

BAGGAGE AND PARCEL INSPECTION

PHYSICAL SPECIFICATIONS

Dimensions: Length: 2,590 mm (102 in.)
Height: 1,345 mm (52.95 in.)*
Width: 840 mm (33.1 in.)
Tunnel Size: 640 mm (W) x 430 mm (H). (25.2 x 16.93 in.)
Conveyor Speed: 0.22 m/sec (44 ft./min)
Maximum Load: 165Kg (365 lbs) evenly distributed
Approximate Weight: Net: 560 Kg (1,232 lbs)
Gross: 760 Kg (1,672 lbs)
System Power: 115 VAC +/- 10% / 60Hz / 10Amps or
230 VAC +/- 10% / 50Hz / 5Amps
Unit is mounted on heavy casters for ease of movement
*Nominal height +1 inch adjustments

GENERAL

Resolution: 38 AWG guaranteed, 40 AWG typical
Penetration: 27 mm guaranteed, 29 mm typical
Material Separation: Low Z, Medium Z, High Z to 0.5 Z accuracy

X-RAY GENERATOR

Cooling: Sealed oil bath with forced air
Anode Voltage: 160KV rated, operating @ 140KV
Tube Current: 0.7 mA typical
Orientation: Vertically upward

COMPUTER SPECIFICATIONS

Processor Speed: Intel Pentium® Processor currently available
Monitor: 17" XGA color, high refresh, non-flicker
Memory: 64 MB RAM minimum
Video Memory: 16 MB minimum
Hard Disk Drive: 40 GB minimum
CD-ROM Drive: 54X
Floppy Disk: 1.44 MB
Access to keyboard port and parallel port is provided by means of a lockable access panel on the outside of the machine.

OPERATING ENVIRONMENT

Storage Temperature: -20°C to 50°C
Operating Temperature: 0°C to 40°C
Relative Humidity: 5 to 95% non-condensing


HEALTH & SAFETY

All Rapiscan Systems products comply with applicable international health and safety regulations including USA FDA X-ray systems (Federal Standard 21CFR 1020.40) and Health and Safety at Work Act 1974-section 6, Amended by the Consumer Protection Act 1987. Maximum leakage radiation less than 0.1mR/hr (1µ Sv/hr) in contact with outer panels.

Film Safety: For ISO 1600/33 DIN, guaranteed up to 10 times exposure to radiation.

CE Compliance: Yes
FCC & IEC Compliance: Yes

With continual development of our products Rapiscan Systems reserves the right to amend specifications without notice.



STANDARD FEATURES	OPTIONS
Crystal Clear™	Flat Panel LCD Monitor
Multi Energy Imaging (4 color)	Enhance Performance X-ray (EPX)
Density Threat Alert	Threat Image Projection (TIP)
Variable Edge Enhancement	TIP Network
High/Low Penetration	Target™-Screener Assist Technology
Variable Gamma	Network Display Station (NDS)
Inverse Video	Network Management System (NMS)
Pseudo Color	Power Conditioner
Variable Density Zoom	Secure Workstation
Organic/Inorganic Stripping	Remote Workstation
Black and White Viewing	Conveyor Accessories
Variable Color Stripping	Foot-mat
Zoom	UPS (Uninterrupted Power Supply)
View previous bag	VCR Output
Manual Image Archiving	Video Printer
Baggage Counter	Automatic Image Archiving
Search Indicator	Auto Reject Unit
Date/Time display	High Penetration
Full diagnostic built in test facility	
Operator Training Program (OTP)	

www.rapiscansystems.com

UNITED STATES OF AMERICA

3232 W. El Segundo Blvd.
Hawthorne, California 90250
UNITED STATES OF AMERICA
Tel: +1 310-978-1457
Fax: +1 310-349-2491
E-mail: sales@rapiscansystems.com

UNITED KINGDOM

X-Ray House
Bonehurst Road
Salfords
Surrey RH1 5GG
UNITED KINGDOM
Tel: +44 (0) 870-7774301
Fax: +44 (0) 870-7774302

ASIA PACIFIC

240 Macpherson Road
#06-04 Pines Industrial Building
Singapore 348574
SINGAPORE
Tel: +65-6743-9892
Fax: +65-6743-9885 / 6743-9915

distributor stamp